

NEUTRO-WASH™

Salt and Chloride Neutralizer

Application Tip Sheet

NEUTRO-WASH™ Salt and Chloride Neutralizer will quickly break down the white powdery film that salt and liquid calcium leave on your equipment, so you can easily rinse it away! NEUTRO-WASH™ will not harm the oil/water separation process or your oil/water separators. NEUTRO-WASH™ is biodegradable and may be flushed down municipal sewers when diluted as recommended.

NEUTRO-WASH™ is a concentrate and will need to be diluted.

Preparation:

NEUTRO-WASH™ can be easily applied through your wash bay pressure washer, portable pressure washer or with RHOMAR's Public Works Applicator.

Note: If you use a **HOT** water pressure washer, **make sure the burner is turned OFF!**

Dilute the concentrated NEUTRO-WASH™ with cold water at a ratio of 1:8.

- One (1) part NEUTRO-WASH™ to eight (8) parts cold water.
- One (1) quart of NEUTRO-WASH™ to two (2) gallons of cold water.

Always follow label instructions.

Use rubber gloves and safety goggles.

Application:

Apply NEUTRO-WASH™ mixture.

Let NEUTRO-WASH™ set for approximately 2 to 3 minutes and watch the corrosive de-icer film melt away.

Rinse NEUTRO-WASH™ off thoroughly with fresh cold water.

Areas of Application:

Salt Spreaders.

Liquid calcium pumps, lines and spray bars.

Loaders and graders.

Undercarriages of vehicles, motor compartments and firewalls.

Anywhere salt comes into contact with your equipment!

NEUTRO-WASH™ is the perfect choice to use before applying protective coatings such as RHOMAR's LUBRA-SEAL® Spreader Encapsulant, MET-CON 3000™ Clear Concrete and Metal Encapsulant or BRIDGE-MATE™ Bridge Component Encapsulant.

CALL TOLL FREE TO REORDER



RHOMAR

solutions@rhomar.com
www.rhomar.com

2107 E Rockhurst St • Springfield, MO 65802

1-800-688-6221

417-866-5592