

PAVE-SAFE™

Asphalt Emulsifier

Application Tip Sheet

PAVE-SAFE™ is a remarkably effective and environmentally responsible alternative to diesel fuel that literally melts away asphalt and road oil spills, splatters and overspray's.

Paving Equipment:

Determine if you have a light or heavy build-up of asphalt or road oil deposits. Heavy is more than 1/4 inch of build-up of asphalt.

- Light Build-Up: Spray on a liberal amount of PAVE-SAFE™ and watch the deposits melt away!
- Heavy Build-Up: Spray on a liberal amount of PAVE-SAFE™ and let it sit for approximately five (5) to ten (10) minutes.

Concrete Cleaning:

PAVE-SAFE™ is also excellent for removing heavy oil and grease deposits from automotive repair center bays where vehicles leak onto floors and vehicle lifts.

PAVE-SAFE™ is remarkable at removing deposits of oil, grease, asphalt and rubber tire marks left by vehicles that stop and leak onto the concrete at customer service bays or payment centers such as toll booths, banks and utility departments. Simply spray PAVE-SAFE™ onto deposits on concrete, agitate with stiff bristled broom and then rinse away.

PAVE-SAFE™ will keep your bays looking great, save your personnel's time and keep you in environmental compliance.

Hand Tools:

Use the Paving Equipment process described above to clean your hand tools.

Remember to always coat your paving tools with PAVE-SAFE™ before you start working with them. This will prevent asphalt build-up.

When a slight asphalt build-up starts to occur, STOP and re-coat your paving tools with PAVE-SAFE™, then continue your shoveling or raking.

Please remember, diesel fuel ends up in your ground water and streams, harming wildlife and eventually making your water undrinkable.

CALL TOLL FREE TO REORDER



solutions@rhomar.com
www.rhomar.com

2107 E Rockhurst St • Springfield, MO 65802

1-800-688-6221

417-866-5592