

RHOMA-SOL™

Asphalt Emulsifier

Application Tip Sheet

RHOMA-SOL™ is a remarkably effective and environmentally responsible alternative to diesel fuel that literally melts away asphalt and road oil spills, splatters and over sprays.

Paving Equipment

Determine if you have a light or heavy build-up of asphalt or road oil deposits. Heavy is more than 1/4 inch of build-up of asphalt.

- Light Build-up: Spray on a light amount of **RHOMA-SOL™** and watch the deposits melt away!
- Heavy Build-up: Spray on a liberal amount of **RHOMA-SOL™** and let it sit for approximately five (5) to ten (10) minutes.

Repeat if necessary. Super heavy build-ups may take two (2) or three (3) applications to reach bare metal.

Rinse thoroughly with water or wipe away the dissolved asphalt deposit. Using a hot, high pressure washer helps to thoroughly flush away loosened deposits. Remember don't rinse **RHOMA-SOL™** off too quickly. It needs time to thoroughly penetrate the asphalt deposit so it can be flushed away.

When using **RHOMA-SOL™** to remove asphalt or road oil deposits from a painted surface, **ALWAYS TEST THE SAFETY OF THE FINISH FIRST** by applying a small amount to an inconspicuous area prior to using it all over. **RHOMA-SOL™** is one of the safest products available, however, if fading or bleaching occurs, use **RHOMA-SOL™** only on unpainted surfaces.

Hand Tools

Use the Paving Equipment process described above to clean your hand tools.

Remember to always coat your paving tools with **RHOMA-SOL™** before you start working with them, this will prevent asphalt build-up.

When a slight asphalt build-up starts to occur, **STOP** and re-coat your paving tools with **RHOMA-SOL™**, then continue your shoveling or raking.

Please remember, diesel fuel ends up in your ground water and streams, harming wildlife and eventually making your water undrinkable.

CALL TOLL FREE TO REORDER



RHOMAR

solutions@rhomar.com
www.rhomar.com

2107 E Rockhurst St • Springfield, MO 65802

1-800-688-6221

417-866-5592