



NEUTRO-WASH™

Neutralizing Salt and Chloride Remover

DESCRIPTION: NEUTRO-WASH™ is specifically designed to neutralize alkaline surfaces and aggressively remove salt, calcium, magnesium chloride and various brines from salt spreaders and related deicing equipment.

USES: NEUTRO-WASH™ is designed to break the bond of all chlorides on all types of salt handling equipment and fleets. NEUTRO-WASH™ is used on salt and sand spreaders, trucks, snow plows and blowers, street sweepers, hydro seeders and any other piece of equipment that comes into contact with salt. NEUTRO-WASH™ is a must when using aggressive deicers such as salt, calcium chloride or magnesium chloride. NEUTRO-WASH™ is the perfect partner when preparing to preserve your equipment inside and out with coatings like LUBRA-SEAL® Spreader Encapsulant or MET-CON 3000™ Clear Equipment Encapsulant.

PREPARATION OF EQUIPMENT: Wash your spreaders, deicing equipment, vehicles or any piece of equipment that comes into contact with salt, calcium chloride or magnesium chloride, to remove any excessive dirt and oil.

APPLICATION OF NEUTRO-WASH™: NEUTRO-WASH™ should be metered through your wash bay or mobile pressure washer. For smaller jobs, use RHOMAR's Public Works Applicators. After normal wash down of your equipment to remove excessive dirt and oil, apply a diluted solution of NEUTRO-WASH™ concentrating on hard to reach areas where salt and chlorides hide.

- 1. ROUTINE MAINTENANCE:** NEUTRO-WASH™ may be diluted up to ½ ounce per gallon for routine maintenance but for aggressive salt and chloride removal, follow steps #2 and #3.
- 2. RHOMAR'S 25-GALLON SPRAYER OR PRESSURE WASHER:** NEUTRO-WASH™ should be metered at a dilution rate of one(1) part NEUTRO-WASH™ to eight (8) parts cold water.

- **REMOVES** - The corrosive white residue from your vehicles and deicing fleet!
- **GREAT** - In your wash bay pressure washers!
- **PREVENTS** - Plugging of tanks, pumps and nozzles!
- **INCREASES** - Equipment life and trade-in value!
- **ALWAYS** - Use NEUTRO-WASH™ before applying LUBRA-SEAL® or MET-CON 3000™

Sold Exclusively By:
RHOMAR Industries Inc
2107 E Rockhurst
Springfield MO 65807 USA

NET CONTENTS 55 GALLONS

- 3. PUBLIC WORKS APPLICATORS:** dilute NEUTRO-WASH™ by using one(1) quart of NEUTRO-WASH™ per two (2) gallons of cold water. Simply let NEUTRO-WASH™ sit for approximately two (2) or three (3) minutes, THEN THOROUGHLY RINSE YOUR EQUIPMENT WITH FRESH WATER.



WARNING

HAZARDS IDENTIFICATION: Causes skin irritation. Causes serious eye irritation.

PREVENTION: Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

RESPONSE:

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call Poison Center or a doctor/physician.

SKIN: Wash with plenty of soap and water. Get medical attention if irritation persists. Take off contaminated clothing and wash before reuse.

INGESTION: Call a doctor/physician if you feel unwell. Rinse mouth.

STORAGE: Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of reach of children.

CONTAINS: Sulfamic Acid, Sodium Hydroxide, Isopropyl Alcohol.

DISPOSAL: Dispose of contents/container in accordance with local, State and Federal regulations.

The recommendations and statements contained herein for use of our products are based on reliable tests, but are not construed as guarantee or warranty either expressed or implied. RHOMAR Industries, Inc. will not be held liable under any circumstances or conditions; either expressed or implied damage in excess of the purchase price of product.

TO REORDER

VISA, MASTER CARD, AND AMERICAN EXPRESS ACCEPTED

1-800-688-6221

solutions@rhomar.com • www.rhomar.com