

ENVIRO-SLIDE® Ultra

Asphalt Release Agent

Application Tip Sheet

ENVIRO-SLIDE® Ultra is a “Next Generation” asphalt release that prevents sticking and adhesion of all asphalts used in road paving, especially the super sticky polymer modified mixes.

ENVIRO-SLIDE® Ultra was specifically developed by Rhomar to be a remarkably effective alternative to diesel fuel, solvents and soap based products to eliminate the sticking of asphalt to dump beds. You may also use ENVIRO-SLIDE® Ultra on your paving construction equipment such as steel or rubber wheeled compactors, shuttle buggies and chutes. ENVIRO-SLIDE® Ultra accomplishes this task **without stripping the oils on your aggregate** and it is **100% biodegradable!**

Beneficial Application Tips

For use in Truck Beds and other Road Paving Equipment

- Start with a clean surface. If your surface has any asphalt build-up at all, use Rhomar's RHOMA-SOL® Bituminous Emulsifier to remove the deposits.
- Dilute ENVIRO-SLIDE® Ultra 5:1 with water for SMA; OGFC or most Polymer Modified Mixes, five (5) parts water and one (1) part ENVIRO-SLIDE® Ultra.
- Dilute ENVIRO-SLIDE® Ultra 20:1 with water for regular HMA mixes, twenty (20) parts water and one (1) part ENVIRO-SLIDE® Ultra. This is the recommended dilution for most asphaltic hot mix. However, since the types of asphaltic mixes and emulsions are so widely varied you can dilute ENVIRO-SLIDE® Ultra as much as 40:1.
- After Dilution agitate ENVIRO-SLIDE® Ultra prior to initial usage.
- Be sure to apply ENVIRO-SLIDE® Ultra immediately prior to picking up each load. Spraying the bed and then driving with no load creates air turbulence in the bed, drying the ENVIRO-SLIDE® Ultra.
- Rhomar recommends the SLIDE-A-MATIC™ Automated Spray System or for manual application use the Rhomar **Heavy Duty Public Works Applicator**, spray on adequate amount, approximately a quart of diluted product for an average dump bed. It is very important to coat every spot of the bed or sticking will occur in any uncoated areas. The **Heavy Duty Public Works Applicator** with it's unique fan spray will greatly aid in this procedure.
- If you are hauling cold mix patching material, re-apply ENVIRO-SLIDE® Ultra to tailgate areas as you remove patch material.

CALL TOLL FREE TO REORDER



RHOMAR

solutions@rhomar.com
www.rhomar.com

2107 E Rockhurst St • Springfield, MO 65802

1-800-688-6221

417-866-5592