

ENVIRO-SLIDE® Ultra

Synthetic "Never-Stick" Asphalt Release Agent

Features:

- ✓ **STOPS ALL ASPHALTS MIXES FROM STICKING** from regular HMA mixes to the super-sticky polymer modifieds. Including SUPERPAVE, OGFC, and SMA!
- ✓ **NO DEGRADATION OF THE OILS ON THE AGGREGATE** synthetic technology meets all state and federal regulations!
- ✓ **NON-FAMMABLE AND TOTALLY BIODEGRADABLE** no potential fines from soil contamination or flash fires!
- ✓ **REDUCES COST PER TON** by diluting up to 1:40 with water giving you great economy!
- ✓ **VERSATILE** made for truck beds, but great in paver boxes, shuttle buggies and on your compactor wheels!

Instructions:

Description:

ENVIRO-SLIDE® Ultra is a revolutionary synthetic asphalt release agent. **ENVIRO-SLIDE® Ultra** was specifically designed to be able to fully release today's super-sticky polymer modified mixes. This list includes: SUPERPAVE, SMA, OGFC, Polymer Modifieds, Crumb Rubber, Permafex, Latex Fiber, all regular HMA, new warm mix HMA and cold mix patching material. **ENVIRO-SLIDE® Ultra** will not break down the oils on the aggregate and meets all local, state and federal regulations.

Uses:

ENVIRO-SLIDE® Ultra is used in truck beds, paver boxes, shuttle buggies, flow boys, live bottom trailers, augers, conveyor systems, chutes, silos, tools and on steel or rubber wheeled compactors or any other piece of equipment that comes into contact with asphalt.

Preparation:

Simply start out with a clean truck bed, paver box, shuttle buggy or compactor wheels. If an asphalt buildup exists, remove it with **RHOMAR'S RHOMA-SOL™**, a powerful asphalt emulsifier that melts away tough asphalt and road oil deposits on contact. **Please Note:** **ENVIRO-SLIDE® Ultra** will not remove existing asphalt deposits.

Application methods:

- **Manually** - **ENVIRO-SLIDE® Ultra** should be applied with RHOMAR'S Public Works Applicator.
- **Automated** - **ENVIRO-SLIDE® Ultra** should be applied with RHOMAR's **SLIDE-A-MATIC™** Release Agent Spray system.

Application:

ENVIRO-SLIDE® Ultra should be applied just prior to picking up your load or working with asphalt. Repeat application with each load.

Recommended dilution rates:

- **SUPERPAVE/Polymer Modifieds Mixes** - Dilute 1:5 with water. One (1) part **ENVIRO-SLIDE® Ultra** to five (5) parts water.
- **Regular HMA Mixes** - Dilute 1:20 with water. One (1) part **ENVIRO-SLIDE® Ultra** to twenty (20) parts water.
- **Cold Mixes for Patching and Repair** - Dilute 1:20 with water. One (1) part **ENVIRO-SLIDE® Ultra** to twenty (20) parts water.

NOTE: Please begin with the recommended dilution rates. With the variety of mixes on the market, dilution rates can be adjusted to achieve optimum results for your particular mix.

CAUTION: KEEP OUT OF REACH OF CHILDREN. Refer to the MSDS (Material Safety Data Sheet) for additional safety information.

The recommendations and statements contained herein for use of our products are based on reliable tests, but are not construed as guarantee or warranty either expressed or implied. RHOMAR Industries, Inc. will not be held liable under any circumstances or conditions either expressed or implied damage in excess of the purchase price of product.



RHOMAR

2107 E. Rockhurst, Springfield, MO 65802
1.800.688.6221 ph 417.866.5592 fx 417.866.5593 email: solutions@rhomar.com

NET CONTENTS.

gallons

**TO REORDER
1.800.688.6221**