



ENVIRO-SLIDE® Ultra

“Never-Stick” Asphalt Release Agent



DESCRIPTION: ENVIRO-SLIDE®Ultra is a revolutionary synthetic asphalt release agent. ENVIRO-SLIDE®Ultra was specifically designed to allow full release of today's super-sticky polymer modified mixes. This list includes: Superpave, SMA, OGFC, Polymer Modified, Crumb Rubber, Permafex, Latex Fiber, all regular HMA, new warm mix HMA and cold mix patching material. ENVIRO-SLIDE®Ultra will not break down the oils on the aggregate and meets all local, state and federal regulations.

USES: ENVIRO-SLIDE®Ultra is used in truck beds, paver boxes, shuttle buggies, flow boys, live bottom trailers, augers, conveyor systems, chutes, silos, tools and on steel or rubber wheeled compactors or any other piece of equipment that comes into contact with asphalt.

PREPARATION OF EQUIPMENT: Simply start out with a clean truck bed, paver box, shuttle buggy or compactor wheels. If any asphalt buildup exists, remove it with Rhomar's RHOMA-SOL™, a powerful asphalt emulsifier that melts away tough asphalt and road oil deposits on contact. Please Note: ENVIRO-SLIDE®Ultra will not remove existing asphalt deposits.

APPLICATION OF ENVIRO-SLIDE®Ultra: Apply ENVIRO-SLIDE®Ultra just prior to picking up your load or working with asphalt. Repeat application with each load.

Recommended dilution rates:

- **Superpave/Polymer Modified Mixes** - Dilute 1:5 with water. One (1) part ENVIRO-SLIDE®Ultra to five (5) parts water.
- **Regular HMA Mixes** - Dilute 1:20 with water. One (1) part ENVIRO-SLIDE®Ultra to twenty (20) parts water.
- **Warm Mix HMA & Cold Mixes for Patching and Repair** - Dilute up to 1:40 with water. One (1) part ENVIRO-SLIDE®Ultra to forty (40) parts water.

Note: Please begin with the recommended dilution rates. With the variety of mixes on the market, dilution rates can be adjusted to achieve optimum results for your particular mix.

- **RELEASES** - All asphalt mixes from regular HMA's to Superpaves!
- **INSPECTOR FRIENDLY** - Meets all State and Federal regulations!
- **NON-FLAMMABLE** - Solves flash fire hazards of petroleum!
- **REDUCES COST** - Per ton with a dilution ratio up to 1:40 with water!
- **100% BIODEGRADABLE** - No soil contamination liability!

Sold Exclusively By:
RHOMAR Industries Inc
2107 E Rockhurst St
Springfield MO 65802 USA

NET CONTENTS: 55 Gallons

METHOD OF APPLICATION:

- **3-GALLON PUBLIC WORKS APPLICATOR** - Always use to manually apply ENVIRO-SLIDE®Ultra.
- **SLIDE-A-MATIC™ Automated Spray System** - Saves time and money by diluting ENVIRO-SLIDE®Ultra to the appropriate dilution rate.



WARNING

HAZARDS IDENTIFICATION: Mildly irritating, may cause eye irritation. May cause upper airway irritation. If swallowed, may cause burns to mouth, throat and/or stomach, may be aspirated resulting in inflammation in lungs.

PREVENTION: Ensure good ventilation. Wear safety glasses with splash shields or face shield. Keep out of reach of children.

RESPONSE:

SKIN: Non-irritating. May cause redness of skin with prolonged contact. Remove contaminated clothing. Wash affected skin areas well with water. If irritation persists, call physician.

EYES: Hold eyelid open and flush with water for at least 15 minutes. Get medical attention immediately. Call physician/specialist.

INHALATION: Irritant, coughing may occur. Move victim to fresh air, rest and keep warm. Apply artificial respiration, if breathing has stopped. Give oxygen if breathing is irregular. Call physician immediately.

INGESTION: Harmful if swallowed. May cause irritation to mouth and throat. If conscious give water or milk to drink. Do not induce vomiting. If victim vomits, turn into recovery position. Get immediate medical attention/call poison control.

STORAGE: Store in tightly closed, clearly labeled containers in cool, well ventilated area.

DISPOSAL: Dispose of contents/container in accordance with local, regional, national and international regulations.

The recommendations and statements contained herein for use of our products are based on reliable tests, but are not construed as guarantee or warranty either expressed or implied. RHOMAR Industries, Inc. will not be held liable under any circumstances or conditions; either expressed or implied damage in excess of the purchase price of product.

TO REORDER

VISA, MASTER CARD, AND AMERICAN EXPRESS ACCEPTED

1-800-688-6221

solutions@rhomar.com • www.rhomar.com