



# PAVE-SAFE™

## HIGH FLASH - LOW VOC ASPHALT EMULSIFIER



**DESCRIPTION:** PAVE-SAFE™ high flash - low VOC asphalt emulsifier is an advanced formulation used by State, County, City Road Departments and Contractors to address today's safety and environmental regulations. PAVE-SAFE™ with its > 350°F high flash, dissolves asphalt and road oils without the use of hazardous solvents. PAVE-SAFE™ is a thixotropic formula, that allows more hang time, aiding in its ability to dissolve the glue molecule, which allows asphalt to adhere to your equipment.

**USES:** PAVE-SAFE™ is the product of choice for removing bituminous deposits of asphalt and road oils from your expensive vehicles, trucks, paving equipment, distributors, truck beds, pothole patchers, shovels, rakes and tools. You can also apply PAVE-SAFE™ to your truck beds, shovels and chutes of your pothole patcher to keep the asphalt from sticking and causing you time-consuming delays.

**METHOD OF APPLICATION:** Applying PAVE-SAFE™ is quick and easy with RHOMAR's Heavy Duty Public Works Applicator! The Heavy Duty Public Works Applicator, with its unique T-JET nozzle and viton seals, gives you a proper application every time without wasting product.

**LIGHT ASPHALT REMOVAL:** For removal of spills, splatters and oversprays on your vehicles and equipment, just spray a light coating of PAVE-SAFE™ onto deposits and let sit for one (1) to five (5) minutes, then pressure wash or steam clean deposits away.

**HEAVY ASPHALT REMOVAL:** for removal of heavy deposits, like those found on spray bars, distributors and under fender wells of trucks, spray PAVE-SAFE™ liberally onto deposits and let sit for fifteen (15) to twenty (20) minutes, then pressure wash or steam clean deposits away.

**APPLICATION NOTE:** PAVE-SAFE™ is safe on most painted surfaces, however always test PAVE-SAFE™ in an inconspicuous spot, prior to usage, for evidence of safety on finish. DO NOT spray PAVE-SAFE™ onto plexiglas or plastic parking light lenses as it will dull the finish.

- **DISSOLVES**  
**Asphalt and road oils on contact!**
- **SAFE**  
**Flash point > 350°F!**
- **LOW VOC's**  
**Plus 100% biodegradable!**
- **CLEANS & PROTECTS**  
**Rakes, shovels and tools!**
- **EFFECTIVE ALTERNATIVE**  
**To diesel and flammable solvents!**
- **SIMPLY PUT, IT WORKS!!**

Sold Exclusively By:  
**RHOMAR Industries Inc**  
2107 E Rockhurst St  
Springfield MO 65802 USA

NET CONTENTS: 55 Gallons

**ALLIED AREAS OF USE:** PAVE-SAFE™ is also amazing for the following jobs: Decal adhesive removal, degreasing engine parts, releasing concrete molds and removal of stubborn grease and oil deposits on concrete floors.



**WARNING**

**HAZARDS IDENTIFICATION:**  
Causes skin and eye irritation.

**PREVENTION:**  
Wear protective gloves and safety glasses as needed. Wash thoroughly after handling.

**RESPONSE:**  
**SKIN:** Wash with plenty of water. Take off contaminated clothing and wash before reuse. If skin irritation occurs, get medical attention.

**EYES:** Rinse cautiously with water for several minutes. Remove contact lenses and continue rinsing. If eye irritation persists, get medical attention.

**INGESTION:** No need for first aid is anticipated if material is swallowed.

**STORAGE:** Store in a cool, dry, well-ventilated place away from direct sunlight and any incompatible materials. Keep container tightly closed.

**DISPOSAL:** Dispose of contents/container in accordance with local, regional, national and international regulations.

The recommendations and statements contained herein for use of our products are based on reliable tests, but are not construed as guarantee or warranty either expressed or implied. RHOMAR Industries, Inc. will not be held liable under any circumstances or conditions; either expressed or implied damage in excess of the purchase price of product.

# TO REORDER

VISA, MASTER CARD, AND AMERICAN EXPRESS ACCEPTED

# 1-800-688-6221

solutions@rhomar.com • www.rhomar.com